

## **1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product name : **Altex Wood Primer**  
Chemical Description : Alkyd Modified  
Supplier : Atlantic Ocean Paint  
Jl. Raya Kepatihan Industri I No.6 A  
Menganti – Gresik. Indonesia.  
Emergency : Telp. 031 - 51203009 ( hunting ) 99008814  
Fax. 031 - 51203099

## **2. HAZARDS IDENTIFICATION**

The vapors are irritating to the eyes, the skin and the respiratory tract. Frequent or continuous skin contact causes irritation and may lead to dermatitis.

The product is flammable.

## **3. PHYSICAL AND CHEMICAL PROPERTIES.**

Physical state : Orange.  
% Solids : 86 % W/W  
Start boiling point : 160 \* ° C  
Melting point : < - 20 ° C  
Relative density : 1.269 kg / dm<sup>3</sup>  
Vapor Pressure : 1 \* mbar ( 20° C )  
Vapor Density : 4.5 \* ( air = 1 )  
Solubility in water : Insoluble  
PH : Not applicable  
Flash point : 42 ° C, Method Abel- Pensky,Closed  
cup  
Autoignition temperature : 230 \* ° C  
\* Derived from the solvents.

## **4. FIRE FIGHTING MEASURES**

Extinguishing Media : Foam, CO<sub>2</sub>, and powder.  
Don't use water.  
Special Risk : Nitrous gasses are produced in case of fire.  
Protective Equipment : Apply self contained breathing apparatus.

## **5. FIRST AID MEASURES.**

General : In all cases of doubt or when symptoms persists seek  
medical advice immediately  
Inhalation : Remove immediately to fresh air, avoid exertion  
Skin contact : Wash immediately with plenty of water and soap  
Remove contaminated clothing  
Eye contact : Rinse for at least 15 minutes with plenty of water  
Ingestion : Give plenty of water to drink, do not induce vomiting.

## **6 HANDLING AND STORAGE**

Apply proper ventilation , possibly combined with a local exhaust. Do not eat, smoke or drink during use. See for personal protection section 8.

Use only explosion proof equipment.

Avoid contact with strong oxidizers: also avoid contact with certain plastics like PVC and natural rubber.

These materials will dissolve.

Keep away from sources of ignition – no smoking. Store at a well-ventilated place

Keep in original, well - closed packaging.

Comply with governmental regulations.

## **7 Toxicological information**

No Experimental data of the product available.

Respiratory exposure to the vapors may lead to coughing, dizziness, sickness, drowsiness and vomiting.

Long term exposure may lead to effects of the central nervous system.

Frequent or continuous skin contact may lead to irritation and dermatitis.

## **8 EXPOSURE CONTROLS / PERSONAL PROTECTIONS**

Wear safety goggles against splashing, at least working clothes and proper gloves ( neoprene or nitril rubber ). Work as much as possible in closed systems. If not feasible install proper ventilation, possibly combined with a local exhaust. Try to reach the lowest possible exposure. Respect the threshold limit values of the dangerous components.

Keep away from food , beverages and tobacco. Wash your hands before a break or leaving work. Put the working clothes away separately.

Launder contaminated clothing before reuse.

## **9 OTHER INFORMATION**

No other information available

This Information only concerns the above mentioned product and need not be valid if used with other products or process.

The information is to our best knowledge correct and complete and is given in good faith but without warranty.

It remains the users own responsibility to make sure that the information is correct and complete for his special use of the product.

---

**ISSUED 05062017 BY ATLANTIC  
THIS MSDS SUPERCEDES THOSE PREVIOUSLY ISSUED**